

SMART⁺ WIFI FLOOD

EXTREMELY LOW-PROFILE AND ROBUST FLOODLIGHTS IN DIFFERENT SIZES – ALSO AVAILABLE WITH RGB FUNCTION





1
SMART+ WIFI FLOOD
50 W



2
SMART+ WIFI FLOOD
30W



3
SMART+ WIFI FLOOD
20W



4
SMART+ WIFI FLOOD
10W



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t ₉₀ ²	W	lm	IP65 ³	K
SMART+ WIFI FLOOD 50 W	4058075474666	1	Dark gray	Aluminum	30000	50.00	4250	A++/A+/A	3000
SMART+ WIFI FLOOD 30W	4058075474642	2	Dark gray	Aluminum	30000	30.00	2190	A++/A+/A	RGB, 3000
SMART+ WIFI FLOOD 20W	4058075474628	3	Dark gray	Aluminum	30000	20.00	1260	A++/A+/A	RGB, 3000
SMART+ WIFI FLOOD 10W	4058075474604	4	Dark gray	Aluminum	30000	10.00	630	A++/A+/A	RGB, 3000

Product name	CRI	°	IP	l ₉₀ ²	b ₉₀ ²	h ₉₀ ²	Beam angle
SMART+ WIFI FLOOD 50 W	≥80	100	IP65	30000	237.0	200.0	36.0
SMART+ WIFI FLOOD 30W	≥80	100	IP65	30000	209.0	168.0	30.0
SMART+ WIFI FLOOD 20W	≥80	100	IP65	30000	152.0	125.0	28.0
SMART+ WIFI FLOOD 10W	≥80	100	IP65	30000	152.0	125.0	28.0

* Works with LEDVANCE WIFI Remote Control. For further information, please see page 368. | ¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).