

## **WORKLIGHTS S-STAND**

HIGHLY FUNCTIONAL AND PORTABLE WORKLIGHTS





1  
LED WORKLIGHT S-STAND  
50 W 4000 K



2  
LED WORKLIGHT S-STAND  
30 W 4000 K



3  
LED WORKLIGHT S-STAND  
20 W 4000 K



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t <sub>90</sub> <sup>2</sup>	W	lm	IP <sub>65</sub> <sup>3</sup>	Temp
LED WORKLIGHT S-STAND 50 W 4000 K	4058075213876	1	Dark gray	Aluminum/Steel	25000	50.00	4500	A++/A+/A	-20...+45
LED WORKLIGHT S-STAND 30 W 4000 K	4058075213852	2	Dark gray	Aluminum/Steel	25000	30.00	2700	A++/A+/A	-20...+45
LED WORKLIGHT S-STAND 20 W 4000 K	4058075213838	3	Dark gray	Aluminum/Steel	25000	20.00	1700	A++/A+/A	-20...+45

Product name	K	CRI	Beam angle	IP	Beam diameter [mm]	Beam length [mm]	Beam height [mm]	Beam width [mm]
LED WORKLIGHT S-STAND 50 W 4000 K	4000	≥80	120	IP65	100000	267.0	272.0	395.0
LED WORKLIGHT S-STAND 30 W 4000 K	4000	≥80	120	IP65	100000	210.0	220.0	325.0
LED WORKLIGHT S-STAND 20 W 4000 K	4000	≥80	120	IP65	100000	166.0	180.0	280.0

<sup>1</sup> The exact terms and conditions can be found at [www.ledvance.com/consumer/services/guarantee](http://www.ledvance.com/consumer/services/guarantee) | <sup>2</sup> Average lifetime in hours | <sup>3</sup> Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).