

LDV TRACK L BK 930

LEDVANCE TRACK L | Indoor LED spotlights



Areas of application

- Spotlighting for shop windows, displays, shelves
- Display lighting
- Salesrooms, counters
- Retail outlets, foyers and museums
- Illumination of sensitive objects
- Art shops, offices, bars
- Galleries, museums

Product benefits

- 5 years guarantee
- Simple and fast connection thanks to universal 3-phase track adapter
- Tool-free installation

Product features

- Color temperature: 3,000 K (Warm White) or 4,000 K (Neutral White)
- Type of protection: IP20
- Lifetime: up to 50,000 h



Product datasheet

Technical data

Electrical data

Operating mode	ECG
Nominal wattage	22.0 W
Nominal voltage	230 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Luminous flux	1200 lm
Light color (designation)	Warm white

Light technical data

Beam angle	10 °
Light distribution	Symmetric

Dimensions & weight

Diameter	97.0 mm
Height	274.0 mm

Colors & materials

Body material	Aluminum
Product color	Traffic black

Certificates & standards

Protection class	I
Type of protection	IP20

Country specific categorizations

Order reference	LDV TRACK L BK
-----------------	----------------

Country specific information

Product code	METEL-Code	SEG number	STK-Number	UK Org
4052899923416	-	7400332	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899923416	LDV TRACK L BK 930	Folding carton box 1	326 mm x 128 mm x 145 mm	6.05 dm ³	1125.00 g
4052899923485	LDV TRACK L BK 930	Shipping carton box 4	347 mm x 276 mm x 321 mm	30.74 dm ³	5492.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

▶ www.osram.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
