

## **ENDURA® STYLE UPDOWN** LED WALL LUMINAIRES IN CLASSIC DESIGN





1  
ENDURA STYLE UpDown  
12 W AL



2  
ENDURA STYLE UpDown  
12 W DG



3  
ENDURA STYLE UpDown  
12 W WT



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t <sub>h</sub> <sup>2</sup>	W	lm	lm <sup>3</sup>	K	CRI	°C
ENDURA STYLE UpDown 12 W AL	4058075205604	1	Aluminum	Aluminum	30000	11.50	700	A++/A+/A	3000	≥80	110
ENDURA STYLE UpDown 12 W DG	4058075214057	2	Dark gray	Aluminum	30000	11.50	700	A++/A+/A	3000	>80	110
ENDURA STYLE UpDown 12 W WT	4058075214071	3	White	Aluminum	30000	11.50	700	A++/A+/A	3000	>80	110

Product name	IP	l <sub>h</sub> <sup>1</sup>	w <sub>h</sub>	h <sub>h</sub>	mm
ENDURA STYLE UpDown 12 W AL	IP44	15000	55.0	90.0	160.0
ENDURA STYLE UpDown 12 W DG	IP44	15000	55.0	90.0	160.0
ENDURA STYLE UpDown 12 W WT	IP44	15000	55.0	90.0	160.0

<sup>1</sup> The exact terms and conditions can be found at [www.ledvance.com/consumer/services/guarantee](http://www.ledvance.com/consumer/services/guarantee) | <sup>2</sup> Average lifetime in hours | <sup>3</sup> Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).