

ENDURA® STYLE UPDOWN DECO

OUTDOOR WALL LED LUMINAIRES WITH
DISTINCTIVE LIGHTING DESIGN





1
ENDURA STYLE UpDown Deco II
11 W DG



2
ENDURA STYLE UpDown Deco I
6 W DG



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t _h ²	W	lm	E _e ³	K	CRI	°C
--------------	------------	-----	-------	----------	-----------------------------	---	----	-----------------------------	---	-----	----

ENDURA STYLE UpDown Deco II 11 W DG	4058075205543	1	Dark gray	Aluminum	30000	10.50	550	A++/A+/A	3000	≥80	55
ENDURA STYLE UpDown Deco I 6 W DG	4058075205529	2	Dark gray	Aluminum	30000	6.00	280	A++/A+/A	3000	≥80	55

Product name	IP	h (mm)	w (mm)	t _h (mm)	Quantity
--------------	----	--------	--------	---------------------	----------

ENDURA STYLE UpDown Deco II 11 W DG	IP44	100000	50.0	140.0	130.0	6
ENDURA STYLE UpDown Deco I 6 W DG	IP44	100000	50.0	100.0	130.0	6

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).