

ENDURA® STYLE SHIELD

UPDOWN LUMINAIRES IN FRESH DESIGN





1
ENDURA STYLE Shield RD
11 W DG



2
ENDURA STYLE Shield SQ
11 W DG



| Product name | GTIN (EAN) | No. | COLOR | MATERIAL | t ₉₀ ² | W | lm | Energy efficiency | K | CRI | IP |
|--------------|------------|-----|-------|----------|------------------------------|---|----|-------------------|---|-----|----|
|--------------|------------|-----|-------|----------|------------------------------|---|----|-------------------|---|-----|----|

| | | | | | | | | | | | |
|--------------------------------|---------------|---|-----------|----------|-------|-------|-----|----------|------|-----|------|
| ENDURA STYLE Shield RD 11 W DG | 4058075205291 | 1 | Dark gray | Aluminum | 30000 | 10.50 | 400 | A++/A+/A | 3000 | >80 | IP44 |
| ENDURA STYLE Shield SQ 11 W DG | 4058075205314 | 2 | Dark gray | Aluminum | 30000 | 10.50 | 410 | A++/A+/A | 3000 | >80 | IP44 |

| Product name | Length (mm) | Width (mm) | Height (mm) | Depth (mm) |
|--------------|-------------|------------|-------------|------------|
|--------------|-------------|------------|-------------|------------|

| | | | | | |
|--------------------------------|-------|------|-------|-------|---|
| ENDURA STYLE Shield RD 11 W DG | 15000 | 60.0 | 240.0 | 142.0 | 6 |
| ENDURA STYLE Shield SQ 11 W DG | 15000 | 60.0 | 240.0 | 142.0 | 6 |

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).