

LED COLOR + WHITE

WALL AND CEILING LUMINAIRES WITH WHITE LIGHT AND RGB FUNCTION – CAN BE REMOTE CONTROLLED





1
LED COLOR + WHITE SQ
400 mm 38 W



2
LED COLOR + WHITE RD
400 mm 38 W



3
LED COLOR + WHITE SQ
200 mm 19 W



4
LED COLOR + WHITE RD
200 mm 19 W



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t _h ²	W	lm	IP ³	K	CRI
LED COLOR + WHITE SQ 400 mm 38 W	4058075265769	1	White	Aluminum	20000	38.00	1900	A++/A+/A	3000	>80
LED COLOR + WHITE RD 400 mm 38 W	4058075265721	2	White	Aluminum	20000	38.00	1700	A++/A+/A	3000	>80
LED COLOR + WHITE SQ 200 mm 19 W	4058075227576	3	White	Aluminum	20000	19.00	780	A++/A+/A	3000	>80
LED COLOR + WHITE RD 200 mm 19 W	4058075227590	4	White	Aluminum	20000	19.00	650	A++/A+/A	3000	>80

Product name	h	IP	l	b	h	d	Weight
LED COLOR + WHITE SQ 400 mm 38 W	110	IP20	100000	400.0	400.0	45.0	4
LED COLOR + WHITE RD 400 mm 38 W	110	IP20	100000	-	-	45.0	4
LED COLOR + WHITE SQ 200 mm 19 W	110	IP20	100000	196.0	196.0	39.0	8
LED COLOR + WHITE RD 200 mm 19 W	110	IP20	100000	-	-	40.0	8

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).