

# LED Panels




ASALITE LED panels with LED light sources are a long-term solution for even, aesthetic and eye-pleasing interior lighting thanks to high-quality, reliable LED chips and the world-renowned LIFUD driver. The LED panel can be placed in a plaster-board ceiling, in an alu frame and with a hanging solution by wires.

As it is also recommended for everyday use, we recommend the product for lightening office buildings, warehouses, meeting rooms, public institutions, schools, halls and garages.

## Asalite Premium LED Panel 60x60 cm 40W 4000K 4800 lumen LIFUD driver

The Asalite LED panel contains reliable LED chips and a world-renowned LiFUD driver. As it is also recommended for everyday use, we recommend the product for lightening hotels, schools, office buildings, hospitals, meeting rooms and public institutions.



**A+**

**LiFUD**


- 40W
- 4800 LUMEN
- 180° LIGHTING ANGLE
- DUST & DAMP PROTECTION **IP20**
- 25 000 HOURS
- 15 000 OFF ON

### TECHNICAL DETAILS

Consumption	40W
LED type	SMD LED
Driver	LIFUD
Luminosity	4800 lumen
Colour temperature	4000K
Dimmable	no
Size	595 x 595 x 10 mm
Lifetime	25 000 hours
Circuit/Frequency	220-240V AC, 50-60Hz
Energy rating	A+
UGR	22
Color rendering index (Ra)	> 80
Power Factor (Pf)	> 0,9
IP Class	IP20
Product code	ASAL0151

## Asalite Premium LED Panel 60x60 cm 45W 4000K 5400 lumen LIFUD NON-FLICKER driver

The Asalite LED panel contains reliable LED chips and a world-renowned LiFUD driver. As it is also recommended for everyday use, we recommend the product for lightening hotels, schools, office buildings, hospitals, meeting rooms and public institutions.



**A+**

**LiFUD**


- 45W
- 5400 LUMEN
- 180° LIGHTING ANGLE
- DUST & DAMP PROTECTION **IP20**
- 25 000 HOURS
- 15 000 OFF ON

### TECHNICAL DETAILS

Consumption	45W
LED type	SMD LED
Driver	LIFUD NON-FLICKER
Luminosity	5400 lumen
Colour temperature	4000K
Dimmable	no
Size	595 x 595 x 10 mm
Lifetime	25 000 hours
Circuit/Frequency	220-240V AC, 50-60Hz
Energy rating	A+
UGR	22
Color rendering index (Ra)	> 80
Power Factor (Pf)	> 0,9
IP Class	IP20
Product code	ASAL0149

## Asalite Premium LED Panel 60x60 cm 40W 4000K 4400 lumen LIFUD driver UGR<19 low glare

The Asalite LED panel contains reliable LED chips and a world-renowned LiFUD driver. As it is also recommended for everyday use, we recommend the product for lightening hotels, schools, office buildings, hospitals, meeting rooms and public institutions.



**A+**

**LiFUD**


- 40W
- 4400 LUMEN
- 180° LIGHTING ANGLE
- POR ÉS PÁRA VÉDELEM **IP20**
- 25 000 HOURS
- 15 000 OFF ON

### TECHNICAL DETAILS

Consumption	40W
LED type	SMD LED
Driver	LIFUD
Luminosity	4400 lumen
Colour temperature	4000K
Dimmable	no
Size	595 x 595 x 10 mm
Lifetime	25 000 hours
Circuit/Frequency	220-240V AC, 50-60Hz
Energy rating	A+
UGR	< 19
Color rendering index (Ra)	> 80
Power Factor (Pf)	> 0,9
IP Class	IP20
Product code	ASAL0175

## Asalite Premium LED Panel 120x30 cm 40W 4000K 4800 lumen LIFUD driver

The Asalite LED panel contains reliable LED chips and a world-renowned LiFUD driver. As it is also recommended for everyday use, we recommend the product for lightening hotels, schools, office buildings, hospitals, meeting rooms and public institutions.



**A+**

**LiFUD**

- 40W
- 4800 LUMEN
- 180° LIGHTING ANGLE
- DUST & DAMP PROTECTION **IP20**
- 25 000 HOURS
- 15 000 OFF ON

### TECHNICAL DETAILS

Consumption	40W
LED type	SMD LED
Driver	LIFUD
Luminosity	4800 lumen
Colour temperature	4000K
Dimmable	no
Size	1195 x 295 x 10 mm
Lifetime	25 000 hours
Circuit/Frequency	220-240V AC, 50-60Hz
Energy rating	A+
UGR	22
Color rendering index (Ra)	> 80
Power Factor (Pf)	> 0,9
IP Class	IP20
Product code	ASAL0152