

## **ENDURA® STYLE MIDI SPOT**

FLEXIBLE OUTDOOR WALL LED SPOTLIGHTS WITH  
ADJUSTABLE LUMINAIRE HEADS





1  
ENDURA STYLE Midi Spot II  
20 W DG



2  
ENDURA STYLE Midi Spot I  
13 W DG



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t <sub>h</sub> <sup>2</sup>	W	lm	Energy efficiency grade	K	CRI	°C
--------------	------------	-----	-------	----------	-----------------------------	---	----	-------------------------	---	-----	----

ENDURA STYLE Midi Spot II 20 W DG	4058075205499	1	Dark gray	Aluminum	30000	20.00	1200	A++/A+/A	3000	≥80	110
ENDURA STYLE Midi Spot I 13 W DG	4058075205475	2	Dark gray	Aluminum	30000	12.50	800	A++/A+/A	3000	≥80	110

Product name	IP	Beam angle	W [mm]	H [mm]	Depth [mm]
--------------	----	------------	--------	--------	------------

ENDURA STYLE Midi Spot II 20 W DG	IP44	15000	168.0	252.0	115.0	6
ENDURA STYLE Midi Spot I 13 W DG	IP44	15000	162.0	125.0	128.0	6

<sup>1</sup> The exact terms and conditions can be found at [www.ledvance.com/consumer/services/guarantee](http://www.ledvance.com/consumer/services/guarantee) | <sup>2</sup> Average lifetime in hours | <sup>3</sup> Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).