

DOT-IT®

UNIVERSAL MINI LED LUMINAIRES WITH VARIABLE MOUNTING





1
DOT-it TOUCH High White



2
DOT-it TOUCH Slim White



3
DOT-it CLASSIC CLASSIC SI



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t_{90} ²	W	lm	Energy efficiency grade ³
DOT-it TOUCH High White	4058075399709	1	White	Acrylonitrile butadiene styrene (ABS)	30000	0.45	32	A++/A+/A
DOT-it TOUCH Slim White	4058075399686	2	White	Acrylonitrile butadiene styrene (ABS)	30000	0.45	32	A++/A+/A
DOT-it CLASSIC CLASSIC SI	4058075227804	3	Silver	Acrylonitrile butadiene styrene (ABS)	20000	0.23	10	A++/A+/A

Product name	K	CRI	Beam angle	IP	Beam diameter [mm]	Beam width [mm]	Beam height [mm]	Beam diameter [mm]	Beam height [mm]
DOT-it TOUCH High White	4000	≥80	120	IP20	15000	-	-	35.0	65.0
DOT-it TOUCH Slim White	4000	≥80	120	IP20	15000	-	-	18.0	65.0
DOT-it CLASSIC CLASSIC SI	7000	>80	70	IP20	15000	-	-	22.0	68.0

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).