

ORBIS® PURE

TIMELESSLY SIMPLE LED CEILING LUMINAIRE





1
ORBIS Pure
400 21 W 3000 K



2
ORBIS Pure
300 16 W 3000 K



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t _h ²	W	lm	E ₊ ³	K	CRI	°C
--------------	------------	-----	-------	----------	-----------------------------	---	----	-----------------------------	---	-----	----

ORBIS Pure 400 21 W 3000 K	4058075260399	1	White	Aluminum	25000	21.00	1500	A++/A+/A	3000	>80	120
ORBIS Pure 300 16 W 3000 K	4058075260375	2	White	Aluminum	25000	16.00	1100	A++/A+/A	3000	>80	120

Product name	IP	h [mm]	d [mm]	Weight
--------------	----	--------	--------	--------

ORBIS Pure 400 21 W 3000 K	IP20	25000	88.0	400.0	6
ORBIS Pure 300 16 W 3000 K	IP20	25000	85.0	300.0	6

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).