

## ENDURA® STYLE ELLIPSE

STYLISH LED LUMINAIRES FOR DIRECT LIGHT





1  
ENDURA STYLE Ellipse  
13 W DG



2  
ENDURA STYLE Ellipse  
900 13 W DG



3  
ENDURA STYLE Ellipse  
500 13 W DG



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t <sub>90</sub> <sup>2</sup>	W	lm	lm/W <sup>3</sup>	K	CRI	°C
ENDURA STYLE Ellipse 13 W DG	4058075205079	1	Dark gray	Aluminum	30000	12.50	890	A++/A+/A	3000	>80	122
ENDURA STYLE Ellipse 900 13 W DG	4058075205116	2	Dark gray	Aluminum	30000	12.50	890	A++/A+/A	3000	>80	122
ENDURA STYLE Ellipse 500 13 W DG	4058075205093	3	Dark gray	Aluminum	30000	12.50	890	A++/A+/A	3000	>80	122

Product name	IP	Beam angle	l [mm]	w [mm]	h [mm]	Qty
ENDURA STYLE Ellipse 13 W DG	IP44	15000	161.0	186.0	75.0	4
ENDURA STYLE Ellipse 900 13 W DG	IP44	15000	75.0	186.0	900.0	2
ENDURA STYLE Ellipse 500 13 W DG	IP44	15000	75.0	186.0	500.0	2

<sup>1</sup> The exact terms and conditions can be found at [www.ledvance.com/consumer/services/guarantee](http://www.ledvance.com/consumer/services/guarantee) | <sup>2</sup> Average lifetime in hours | <sup>3</sup> Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEL) on a scale of A++ (highest efficiency) to E (lowest efficiency).