

SUBMARINE® INTEGRATED

DAMP-PROOF LUMINAIRES WITH INTEGRATED LED MODULE





1
SubMARINE Integrated
600 18 W 4000 K



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t[h] ²	W	lm	IP ³	Temp
--------------	------------	-----	-------	----------	-------------------	---	----	-----------------	------

SubMARINE Integrated 1500 48 W 4000 K	4058075260498	1	Gray	Polycarbonate (PC)	30000	48.00	4000	A++/A+/A	-20...+40
SubMARINE Integrated 1200 36 W 4000 K	4058075260412	1	Gray	Polycarbonate (PC)	30000	36.00	3000	A++/A+/A	-20...+40
SubMARINE Integrated 600 18 W 4000 K	4058075260351	1	Gray	Polycarbonate (PC)	30000	18.00	1500	A++/A+/A	-20...+40

Product name	K	CRI	IP	L [mm]	w [mm]	h [mm]	Icons
--------------	---	-----	----	--------	--------	--------	-------

SubMARINE Integrated 1500 48 W 4000 K	4000	>80	IP65	1480.0	86.0	72.0	8
SubMARINE Integrated 1200 36 W 4000 K	4000	>80	IP65	1180.0	86.0	66.0	8
SubMARINE Integrated 600 18 W 4000 K	4000	>80	IP65	590.0	86.0	66.0	8

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEl) on a scale of A++ (highest efficiency) to E (lowest efficiency).