

LED BULKHEAD

VERSATILE, EASY TO INSTALL FUNCTIONAL LUMINAIRES





1
LED BULKHEAD
11 W 4000 K WT



2
LED BULKHEAD
11 W 4000 K BK



3
LED BULKHEAD
6 W 4000 K WT



4
LED BULKHEAD
6 W 4000 K BK



Product name	GTIN (EAN)	No.	COLOR	MATERIAL	t ₉₀ ²	W	lm	IP ₆₅ ³	Temp
LED BULKHEAD 11 W 4000 K WT	4058075271661	1	White	Polycarbonate (PC)	20000	11.00	800	A++/A+/A	-20...+40
LED BULKHEAD 11 W 4000 K BK	4058075271685	2	Black	Polycarbonate (PC)	20000	11.00	800	A++/A+/A	-20...+40
LED BULKHEAD 6 W 4000 K WT	4058075271586	3	White	Polycarbonate (PC)	20000	5.50	450	A++/A+/A	-20...+40
LED BULKHEAD 6 W 4000 K BK	4058075271647	4	Black	Polycarbonate (PC)	20000	5.50	450	A++/A+/A	-20...+40

Product name	K	CRI	IP	Beam angle	l _{ax} ¹	w _{ax} ¹	h _{ax} ¹	Beam diameter
LED BULKHEAD 11 W 4000 K WT	4000	≥80	IP54	120	216.0	143.0	79.0	6
LED BULKHEAD 11 W 4000 K BK	4000	≥80	IP54	120	216.0	143.0	79.0	6
LED BULKHEAD 6 W 4000 K WT	4000	≥80	IP54	120	168.0	117.0	70.0	8
LED BULKHEAD 6 W 4000 K BK	4000	≥80	IP54	120	168.0	117.0	70.0	8

¹ The exact terms and conditions can be found at www.ledvance.com/consumer/services/guarantee | ² Average lifetime in hours | ³ Energy efficiency grade of the permanently integrated, non-exchangeable LED modules. Energy efficiency index (EEI) on a scale of A++ (highest efficiency) to E (lowest efficiency).