

## ULTRA LIFE P21W

Up to four times longer lifetime




### Extra lifetime

Up to four times longer lifetime compared to standard auxiliary lamps



### More durability

For longer replacement cycles and additional reliability and comfort



### Wide product range

Fits for most common auxiliary lamp types



### The durable light with up to four times longer lifetime

With ULTRA LIFE, you choose durable signal lamps for your car. The lamps provide a long life span - up to four times longer lifetime compared to standard lamps - and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). They are therefore ideal for frequent drivers.

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

General Product Information

Global order reference	7506ULT
------------------------	---------


Electrical Data

Power input	25 W
Nominal voltage	12 V
Nominal wattage	21 W
Test voltage	13.5 V
Power input tolerance	±6 %

Photometric Data

Nominal luminous flux	460 lm
Luminous flux tolerance	±15 %

Physical Attributes & Dimensions



Diameter	25.0 mm
Product weight	7.88 g
Length	52.5 mm
Lamp base	BA15s

Lifetime Data

Lifespan B3	500 hr
Lifespan Tc	1000 hr

Product datasheet

Capabilities

Technology	AUX
------------	-----

Certificates & standards

ECE category	P21W
Approval marks – approval	E1 approval

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321415141   4062172394833   4008321415349
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	No declarable substances contained

Country specific information


Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321415349	OSRA7506ULT	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321415349	ULTRA LIFE P21W	Unpacked 1	52 mm x 25 mm x 25 mm	0.35 dm <sup>3</sup>	8.00 g
4008321415363	ULTRA LIFE P21W	Shipping carton box 50	273 mm x 145 mm x 65 mm	2.57 dm <sup>3</sup>	554.00 g
4062172394833	ULTRA LIFE P21W	BLI ECO 2	95 mm x 27 mm x 135 mm	0.35 dm <sup>3</sup>	26.00 g
4062172394840	ULTRA LIFE P21W	Shipping carton box 20	156 mm x 144 mm x 110 mm	2.47 dm <sup>3</sup>	308.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions

	ref_pim_amsproduct360degreeimages ULTRA LIFE P21W 7506ULT
---	--

**Application advice**

For more detailed application information and graphics please see product datasheet.

**Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



**OSRAM**