

# XENARC NIGHT BREAKER 220 D4S



Up to 220% more brightness<sup>1)</sup> Compared to minimum ECE R98/R99 requirements

More light allows to see farther and therefore react sooner compared to the minimum legal standard



Up to 250 m long beam

For better visibility



Up to 220% more brightness<sup>1)</sup> Compared to minimum ECE R98/R99 requirements

More modern look compared to the minimum legal standard



The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

# Product datasheet

## Technical data


### Electrical Data

Power input	35 W
Nominal voltage	42 V
Nominal wattage	35 W
Test voltage	13.5 V
Power input tolerance	±3 %

### Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %

### Physical Attributes & Dimensions



Diameter	9 mm
Diameter	9 mm
Product weight	16.30 g
Length	77.3 mm
Lamp base	P32d-5

### Lifetime Data

Lifespan B3	2000 hr
Lifespan Tc	3000 hr

### Capabilities

Technology	HID <sup>1)</sup>
------------	-------------------

<sup>1)</sup> High-intensity discharge lamp

### Certificates & standards

## Product datasheet

ECE category	D4S <sup>1)</sup>
--------------	-------------------

1) To be operated only with approved electronic control gear

### Environmental & Regulatory Information

#### Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Primary article identifier 4062172398701 | 4062172397827

Declaration no. in SCIP database In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172397827	XENARC NIGHT BREAKER 220 D4S	HFB ECO 2	100 mm x 51 mm x 120 mm	0.23 dm <sup>3</sup>	62.00 g
4062172397834	XENARC NIGHT BREAKER 220 D4S	Shipping carton box 4	113 mm x 111 mm x 134 mm	1.68 dm <sup>3</sup>	167.00 g
4062172398701	XENARC NIGHT BREAKER 220 D4S	Folding carton box 1	53 mm x 46 mm x 93 mm	0.23 dm <sup>3</sup>	36.00 g
4062172398718	XENARC NIGHT BREAKER 220 D4S	Shipping carton box 4	115 mm x 101 mm x 103 mm	1.20 dm <sup>3</sup>	177.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 User instruction GPRS_Safety symbols instructions
 ref_pim_amsp_product360degreeimages XENARC NIGHT BREAKER D4S 66440XNB

#### Safety advice

XENARC lamps should be replaced by a qualified mechanic. This product must only be operated with approved electronic control gear.

#### Legal advice

Light output compared to the minimum ECE R112/R37 requirements. This product must only be operated with approved electronic control gear. XENARC lamps should be replaced by a qualified mechanic. Reduced UV emission | For projection headlights | ECE approval and DOT label ± 450 lm.

#### Application advice

## Product datasheet

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**OSRAM**